



UNIVERSITI PUTRA MALAYSIA

**PHYSICAL AND THERMAL CHARACTERIZATION OF GLASS
CERAMICS PREPARED FROM CULLET AND COAL BOTTOM ASH**

MOHD ZUL HILMI BIN MAYZAN

FS 2010 35

**PHYSICAL AND THERMAL CHARACTERIZATION OF GLASS
CERAMICS PREPARED FROM CULLET AND COAL BOTTOM ASH**

By

MOHD ZUL HILMI BIN MAYZAN

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,
in Fulfilment of the Requirements for the Degree of Master of Science**

September 2010



DEDICATION

TO MY FAMILY

Mayzan bin Mansor

Norhana binti Nayan

Mohd Zulfadhli bin Mayzan

And my loving memories to

Mohamad Zul Fahmi bin Mayzan

Thank you for the inspiration and encouragement in everything I do

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**PHYSICAL AND THERMAL CHARACTERIZATION OF GLASS
CERAMICS PREPARED FROM CULLET AND COAL BOTTOM ASH**

By

MOHD ZUL HILMI BIN MAYZAN

September 2010

Chairman: Associate Professor Zaidan Abdul Wahab, PhD

Faculty: Science

This thesis describes the physical and thermal characterization of glass ceramics prepared from mixtures of soda lime cullet glass and coal bottom ash. The aim of this research is to develop and optimize the phase and structural properties, microstructure, density, linear shrinkage and Vickers micro hardness as well as to determine the thermal diffusivity behavior of glass ceramics. Three batch compositions of glass ceramics were obtained by mixing 50-90 weight percent of soda lime cullet glass with 10-50 weight percent of coal bottom ash, undergone the vitrification method by melting the compositions at 1450°C for 3 hours and heat treating the compacted powdered glasses between 700 and 1000°C for 2 hours at 100°C intervals. The vitrification method offered a solution for the disposal of soda lime cullet glass and coal bottom ash as well as to minimize their hazardous effects to the environment.

The resulting samples were characterized by using several characterization techniques involving X-ray fluorescence spectroscopy, differential thermal analysis, X-ray diffraction, scanning electron microscope with energy dispersive X-ray, optical microscope, density, linear shrinkage, Vickers micro hardness and thermal diffusivity determination by using flash method. The differential thermal analysis on all powdered glasses revealed that the crystallization temperature occur above 700°C. The crystalline phases were identified as wollastonite [CaSiO₃], augite, aluminian [Ca(Mg,Fe,Al)(Si,Al)₂O₆] and albite, disordered [NaAlSi₃O₈]. Wollastonite crystals had whisker-type with acicular grains and needle-like morphologies, augite, aluminian crystals had feather-like and small oval-like morphologies while samples that have crystalline phases of augite, aluminian and albite, disordered had scratch-like morphologies. The measured density, linear shrinkage, Vickers micro hardness and thermal diffusivity for all heat treated samples were in range of 2.70 to 2.76 g/cm³, 0.83 to 14.04 %, 496.2 to 747.9 kg/mm² and 0.133 to 0.766 mm²/s respectively. Generally, the glass content in heat treated samples is responsible in reducing the density, Vickers micro hardness and thermal diffusivity values. According to the findings in all characterization techniques, the most promising heat treated samples at each batch composition were suitable for industrial use, especially in the manufacturing of tiles.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Master Sains

**PENCIRIAN FIZIKAL DAN TERMA SERAMIK KACA DISEDIAKAN
DARIPADA KEPINGAN KACA DAN ABU BAWAH ARANG BATU**

Oleh

MOHD ZUL HILMI BIN MAYZAN

September 2010

Pengerusi: Profesor Madya Zaidan Abdul Wahab, PhD

Fakulti: Sains

Tesis ini memperihalkan pencirian fizikal dan terma seramik kaca disediakan daripada pelbagai campuran kepingan kaca kapur soda dan abu bawah arang batu. Tujuan penyelidikan ini adalah untuk menghasilkan dan mengoptimumkan sifat-sifat fasa dan stuktur, mikrostruktur, ketumpatan, pengecutan linear dan kekerasan mikro Vickers serta menentukan kelakuan kerosapan terma seramik kaca. Tiga kumpulan komposisi seramik kaca diperolehi daripada campuran 50-90 peratus berat kepingan kaca kapur soda dengan 10-50 peratus berat abu bawah arang batu, menjalani kaedah pengkacaan dengan meleburkan komposisi-komposisi tersebut pada 1450°C selama 3 jam dan perawatan haba serbuk kaca yang dipadatkan pada julat suhu diantara 700 dan 1000°C selama 2 jam pada selang 100°C. Kaedah pengkacaan menawarkan penyelesaian untuk melupuskan kepingan kaca kapur soda dan abu bawah arang batu serta meminimumkan kesan yang berbahaya terhadap alam sekitar.

Sampel-sampel yang diperolehi dicirikan dengan menggunakan beberapa teknik pencirian membabitkan spektroskopi pendarflour sinar-X, analisis pembezaan terma, pembelaan sinar-X, mikroskop pengimbas elektron dengan sebaran tenaga sinar-X, mikroskop optikal, ketumpatan, pengecutan linear, kekerasan mikro Vickers dan keresapan terma yang ditentukan menggunakan kaedah lampu kilat. Analisis pembezaan terma pada semua serbuk kaca menjelaskan bahawa suhu penghabluran berlaku selepas 700°C. Fasa-fasa hablur yang dikenal pasti adalah wollastonite [CaSiO_3], augite, aluminian [$\text{Ca}(\text{Mg,Fe,Al})(\text{Si,Al})_2\text{O}_6$] dan albite, celaru [$\text{NaAlSi}_3\text{O}_8$]. hablur wollastonite mempunyai bentuk seperti misai dengan butir-butir menjarum dan bentuk jejarum, hablur augite, aluminian mempunyai bentuk seperti bulu pelepah dan bujur kecil manakala sampel-sampel yang mempunyai fasa hablur augite, aluminian dan albite, celaru mempunyai bentuk seperti kesan calar. Pengukuran ketumpatan, pengecutan linear, kekerasan mikro Vickers dan keresapan terma untuk semua sampel yang telah melalui rawatan haba adalah masing-masing dalam lingkungan 2.70 hingga 2.76 g/cm³, 0.83 hingga 14.04 %, 496.2 hingga 747.9 kg/mm² dan 0.133 hingga 0.766 mm²/s. Pada amnya, kandungan kaca pada sampel-sampel yang telah menjalani rawatan haba bertanggungjawab merendahkan nilai ketumpatan, kekerasan mikro Vickers dan keresapan haba. Menurut penemuan pada semua teknik-teknik pencirian, sampel-sampel yang terbaik selepas menjalani rawatan haba pada setiap kumpulan komposisi adalah sesuai untuk kegunaan industri, terutamanya dalam pembuatan jubin.

ACKNOWLEDGEMENTS

First and foremost, I would like to extend my deepest praise to Allah S.W.T., the Almighty, who has given me strength, patience, courage and maturity to write this thesis. My deepest praise also goes to Prophet Muhammad S.A.W for his advices and guideline, which always useful while accomplishing this thesis.

It is of great pleasure to express my heartfelt thanks and earnest gratitude to my supervisor, Assoc. Prof. Dr. Zaidan Abdul Wahab for his superb guidance, encouragement, valuable advice and insightful editorial skills while examining my thesis. I would like to extend my sincere appreciation to my co-supervisor, Dr. Khamirul Amin Matori for his guidance and helpful discussion especially during the period of sample preparation. Special thanks to Prof. Dr. Sidek Ab. Aziz and Dr. Halimah Mohamed Kamari for their invaluable suggestions and opinions.

Warm thanks to my family for their unconditional love; all my friends who have directly or indirectly contributed toward the success of this research; all staffs in Physics Department for their co-operation and my fellow colleagues in UTHM for their constant sharing of knowledge throughout the journey in completing my study. Lastly, a million thanks to UTHM and Ministry of Higher Education Malaysia for the financial support, which enable me to complete my study. Thank you.



I certify that a Thesis Examination Committee has met on 20th September 2010 to conduct the final examination of Mohd Zul Hilmi bin Mayzan on his thesis entitled “Physical and Thermal Characterization of Glass Ceramics Prepared from Cullet and Coal Bottom Ash” in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the degree of Master of Science.

Members of the Thesis Examination Committee were as follows:

Azmi Zakaria, PhD

Professor
Faculty of Science
Universiti Putra Malaysia
(Chairman)

Sidek Ab. Aziz, PhD

Professor
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Halimah Mohamed Kamari, PhD

Lecturer
Faculty of Science
Universiti Putra Malaysia
(Internal Examiner)

Ibrahim Abu Talib, PhD

Professor
Faculty of Science and Technology
Universiti Kebangsaan Malaysia
(External Examiner)

BUJANG KIM HUAT, PhD

Professor and Deputy Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirement for the degree of Master of Science. The members of the Supervisory Committee were as follows:

Zaidan Abdul Wahab, PhD

Associate Professor
Faculty of Science
Universiti Putra Malaysia
(Chairman)

Khamirul Amin Matori, PhD

Lecturer
Faculty of Science
Universiti Putra Malaysia
(Member)

HASANAH MOHD GHAZALI, PhD

Professor and Dean
School of Graduate Studies
Universiti Putra Malaysia

Date:



DECLARATION

I declare that the thesis is my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously, and is not concurrently, submitted for any other degree at Universiti Putra Malaysia or at any other institution.

MOHD ZUL HILMI BIN MAYZAN

Date: 20 September 2010

TABLE OF CONTENTS

	Page
DEDICATION	ii
ABSTRACT	iii
ABSTRAK	v
ACKNOWLEDGEMENTS	vii
APPROVAL	viii
DECLARATION	x
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF ABBREVIATIONS	xviii

CHAPTER

1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Objective of Study	4
	1.3 Chapter Organization	5
2	LITERATURE REVIEW AND THEORY	7
	2.1 Glass and Glass Ceramics from Wastes	7
	2.2 Method for Glass Preparation	10
	2.3 Processing Routes for Glass Ceramics Production	12
	2.3.1 Conventional Method (Two Stage Heat Treatment)	12
	2.3.2 Modified Conventional Method (Single Stage Heat Treatment)	14
	2.3.3 Petrurgic Method	15
	2.3.4 Powder Method	16
	2.4 Characterization of Glass Ceramics Material	18
	2.4.1 Chemical Compositions of the Raw Material	18
	2.4.2 Crystallization of Glass	21
	2.4.3 Application Perspective	23
	2.5 Various Techniques to Determine Thermal Diffusivity	25
	2.6 Flash Method – Theoretical Consideration	26
	2.6.1 Physical Model	27
	2.6.2 Mathematical Interpretation	27
	2.6.3 Ways for Thermal Diffusivity Determination	31
	2.7 Heat Transport Properties of Solids	35



3	METHODOLOGY	38
3.1	Introduction	38
3.2	Sample Preparation	38
3.2.1	Preparation of Raw Materials	40
3.2.2	Weighing – Preparing Batch Compositions	41
3.2.3	Dry Milling	42
3.2.4	Glass Melting and Quenching	42
3.2.5	Powder Processing	43
3.2.6	Pressing – Circular Pellet Form	44
3.2.7	Heat Treatment Process of Glass Pellets	45
3.3	Sample Characterization	46
3.3.1	Chemical Compositions	47
3.3.2	Crystallization Behavior	48
3.3.3	Phase and Structural Properties	49
3.3.4	Microstructure	50
3.3.5	Density	52
3.3.6	Linear Shrinkage	53
3.3.7	Vickers Micro Hardness	54
3.3.8	Thermal Diffusivity	56
4	RESULTS AND DISCUSSION	60
4.1	Introduction	60
4.2	Chemical Analysis	61
4.3	DTA Analysis	63
4.4	Overview of Heat Treated Samples	65
4.5	Phase and Structural Analysis	67
4.5.1	90SLCG10CBA	67
4.5.2	70SLCG30CBA	70
4.5.3	50SLCG50CBA	72
4.5.4	Further Discussion	74
4.6	Microstructure Analysis	76
4.6.1	90SLCG10CBA	76
4.6.2	70SLCG30CBA	84
4.6.3	50SLCG50CBA	90
4.7	Density, Linear Shrinkage and Vickers Micro Hardness Analysis	97
4.8	Thermal Diffusivity Analysis	104
4.8.1	90SLCG10CBA	104
4.8.2	70SLCG30CBA	107
4.8.3	50SLCG50CBA	109
4.8.4	Further Discussion	111
5	CONCLUSION AND RECOMMENDATIONS	114
5.1	Introduction	114



5.1.1	Production of Glass and Glass Ceramics Materials	114
5.1.2	Optimization of Heat Treated Samples	116
5.1.3	Thermal Diffusivity Behavior of Heat Treated Samples	118
5.2	Recommendations for Future Work	119
REFERENCES		120
APPENDICES		127
A1	EDX Spectra for Batch 90SLCG10CBA	127
A2	EDX Spectra for Batch 70SLCG30CBA	129
A3	EDX Spectra for Batch 50SLCG50CBA	131
BIODATA OF STUDENT		133
LIST OF PUBLICATIONS/CONFERENCES		134

